

## DECLARATION OF PERFORMANCE Nº 001DOPPORCEDOS

**1.Unique identification code of the product-type :** Dry pressed ceramic tiles, with water absorption  $E_b \leq 0,5\%$ .

**2.Intended use/es:** For internal and external walls and floorings

**3.Manufacturer:**

PORCELANITE DOS SL

Camino Foyes Ferraes S/Nº

12110 Alcora (Castellón)-Spain

**4.System/s of AVCP :** System 4

**5.Harmonised standard:** EN14411

**6.Notified body/ies:** Not applicable

**7.Declared performances:**

Essential characteristics	Performance
Reaction to fire	A1 <sub>FL</sub> /A1
Release of dangerous substance, for: - Cadmium - Lead	<0,1 mg/dm <sup>2</sup> <0,1 mg/dm <sup>2</sup>
Breaking strength	>1300 N
Slipperiness:	PDN
Tactility	NPD
Bond strength/adhesión, for: Cementitious adhesive, type C2	>1N/mm <sup>2</sup>
Thermal shock resistance	Pass
Durability for: -internal use: -external use: freeeze-thaw resistance	Pass Pass

PND: No performance determined.

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Porcelanite Dos SL

Sonia Moliner Pejó

Administradora

Alcora, 2<sup>nd</sup> May , 2023

PORCELANITE<sup>®</sup>DOS  
cerámicas  
Cno. Foyes Ferraes S/Nº 12110 ALCORÁ (CS)  
Tel.: 964 36 11 95 Fax: 964 36 05 88  
C.I.F. B-13429230